

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

09/743774



GB00
08837



PCT/GB 00 / 0 2 2 3 7



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)


REC'D 25 JUL 2000	
WIPO	PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed 
Dated 06 July 2000

Patents Act 1977
(16)

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

02JUN00 E54 The Patent Office
P01/7700 Cardiff Road
Newport
Gwent NP10 0QQ



1. Your reference

P/61815:GBP

2. Patent application number
(The Patent Office will fill in this part)

0013323.1

02 JUN 2000

3. Full name, address and postcode of the or of each applicant (underline all surnames)

MARCONI COMMUNICATIONS LIMITED
P O BOX 53, NEW CENTURY PARK
COVENTRY
CV3 1HJ

Patents ADP number (*if you know it*)
If the applicant is a corporate body, give the country/state of its incorporation

ENGLAND

7519200001

4. Title of the invention

MESH NETWORKS

5. Name of your agent (*if you have one*)

H A BRANFIELD

"Address for service" in the United Kingdom to which all correspondence should be sent

MARCONI INTELLECTUAL PROPERTY
WATERHOUSE LANE
CHELMSFORD
ESSEX CM1 2QX

(including the postcode)

Patents ADP number (*if you know it*)

7710094001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country	Priority application number (<i>if you know it</i>)	Date of filing (day / month / year)
GB	9913990.9	17.06.99

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

YES

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body
- See note (d)

9. Enter the number of sheets any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 3

Claim(s) 2

Abstract 1

Drawing(s) 6

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 1

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77) 1

Any other documents
(Please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature
H A BRANFIELD

Date
31.05.2000

12. Name and daytime telephone number of person to contact in the United Kingdom

H A BRANFIELD

01245 275132

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

~~DUPLICATE~~

MESH NETWORKS

In networks, such as telecommunication networks, fully meshed networks are often used to interconnect the nodes together and in particular to interconnect trunk exchanges. Although fully meshed networks can be of considerable use, they do have the characteristic that the more nodes there are in a fully meshed network, then the narrower the routes between nodes have to be once the switches are port limited. Doubling the nodes in a fully meshed network can halve the size of each route across the mesh. However, reducing the route size can increase the chance of blocking as well as reducing the Erlang efficiency.

In some telecommunication networks each fully meshed trunk exchange is also connected to several local exchanges, so that the longer distance trunk calls tend to traverse four exchanges namely a local, a trunk, a second trunk and a final local.

In such a network the local exchanges only need to know if a call originating on its own exchange cannot be terminated on its own exchange, in which case the call is forwarded to a trunk exchange.

For reasons of redundancy a local exchange is normally connected to more than one trunk exchange, in which case a call which cannot be terminated on its own exchange can probably be forwarded to any of the connected trunk exchanges.

However if the local exchanges are connected to more trunk exchanges than are needed for redundancy reasons, then the local exchange could be asked to perform part of the overall trunk routing algorithm. Consequently the intended final destination of the call can be used to decide to which trunk exchange the call should be sent to by the local exchange.

Provided the local exchange is able to route to more than one trunk exchange depending on the destination of the call, then it is possible to use a pair of trunk exchanges to perform the function of one existing trunk exchange, with approximately twice the capacity and throughput. This is assuming that the two exchanges each have the same or similar capacity to the existing trunk exchange. The existing trunk exchange can be one of the pair of trunk exchanges. The pair of trunk exchanges can be known as Siamese trunk exchanges.

According to the present invention there is provided a telecommunications network comprising a plurality of mesh nodes, each mesh node including one or more switches, at least one of the mesh nodes including a plurality of switches, each mesh node having a connection to each other mesh node by means of a connection between a switch at the one mesh node and a switch at the other mesh node and each mesh node having associated therewith a respective plurality of local nodes, each switch of each mesh node being connected to all of the respective associated plurality of local nodes and including a network routing algorithm to control the routing in the network

There is further provided a method of upgrading a telecommunications network, said telecommunications network comprising a plurality of mesh nodes, wherein each mesh node includes at least one switch, each mesh node having a direct connection to each other mesh

node by means of a connection between a switch at the one mesh node and a switch at the other mesh node and the switch or switches of each mesh node being each connected to all of a respective plurality of multiple local nodes, the method comprising the steps of :-

- (a) adding a further switch to at least one of the mesh nodes;
 - (b) connecting all of the respective plurality of local nodes to the further switch;
 - (c) providing a network routing algorithm to control the routing in the network;
- and
- (d) dividing the connections from the at least one mesh node to the switches of the other mesh nodes between the switch or switches and the further switch of the at least one mesh node.

The present invention will now be described by way of example, with reference to the accompanying drawings in which:

Figure 1 shows an example of a network having a number of fully meshed mesh nodes;

Figure 2 shows an example of a fully meshed mesh node of the network shown in Figure 1 connected to multiple local nodes;

Figure 3 shows an example of a fully meshed mesh node of the network shown in Figure 1 with a single switch;

Figure 4 shows an example of a fully meshed mesh node of the network shown in Figure 1 with two unconnected switches;

Figure 5 shows an example of a fully meshed mesh node of the network shown in Figure 1 with two connected (Siamese) switches; and

Figure 6 shows an example of a network as shown in Figure 1 including a number of fully meshed mesh nodes where each node has two switches.

Figure 1 shows an example of a network having fully meshed mesh nodes, such as trunk exchanges, where each mesh node is directly connected to every other mesh node. In practice these links are often carried by transmission systems.

In Figure 2 some of the mesh nodes (trunk exchanges) of Figure 1 are shown connected to multiple local nodes, such as local exchanges. In practice these connections are often carried by transmission systems. The connection of multiple local exchanges to trunk exchanges is a recognised telecommunication network configuration.

Figure 3 shows a mesh node of Figure 2 containing a single switch. Such a switch could be a trunk exchange equipment. This switch is connected to all the other mesh Nodes as well as all the illustrated multiple Local Nodes. The illustrated Local Nodes may also be connected to switches at other mesh nodes.

Figure 4 shows the mesh node of Figure 3, to which has been added a further switch. Any added switches could be trunk exchanges. The direct links from the other mesh nodes are taken to one or the other, but not both, of the switches. The pair of switches are both connected to all the multiple local nodes associated with that mesh node. The local nodes have to be able to route calls or messages to the appropriate one of the pair of switches.

Figure 5 shows the mesh node containing two switches as in Figure 4, but with a connection (Siamese link) between them. If the connection between an local node and the switch that is normally used to route a call or message is congested, then if the connection to the other one

of the pair of switches is not congested then this connection and the Siamese link can be used in series, to avoid the congestion. The Siamese link is not essential, but can be a useful feature for practical networks.

Figure 6 shows an example of a network where all the Mesh Nodes each have two switches, each pair of switches within a mesh node being joined by a Siamese link. The overall result is that each switch is connected to approximately one half of the other mesh nodes and approximately one quarter of the other switches. For larger examples the approximations can be more precise, but there is no basic need to equally divide the routes between the mesh nodes and the switches. Some routes may naturally carry more traffic and some pairs of switches may not have identical characteristics to each other.

The network will require a network routing algorithm to control the routing of messages, of whatever form through the network.

CLAIMS

1. A telecommunications network comprising a plurality of mesh nodes, each mesh node including one or more switches, at least one of the mesh nodes including a plurality of switches, each mesh node having a connection to each other mesh node by means of a connection between a switch at the one mesh node and a switch at the other mesh node and each mesh node having associated therewith a respective plurality of local nodes, each switch of each mesh node being connected to all of the respective associated plurality of local nodes and the network including a network routing algorithm to control the routing in the network.
2. A telecommunications network as claimed in Claim 1, wherein one or more local nodes are connected to more than one mesh node.
3. A telecommunications network as claimed in Claim 1 or 2, wherein the plurality of switches of a mesh node are connected.
4. A telecommunications network substantially as hereinbefore described, with reference to and as illustrate in Figures 4, 5 and 6 of the accompanying drawings.
5. A method of upgrading a telecommunications network, said telecommunications network comprising a plurality of mesh nodes, wherein each mesh node includes at least one switch, each mesh node having a direct connection to each other mesh node by means of a connection between a switch at the one mesh node and a switch at the other mesh node and the switch or switches of each mesh node being each connected to all of a respective plurality of multiple local nodes, the method comprising the steps of :-
 - (a) adding a further switch to at least one of the mesh nodes;
 - (b) connecting all of the respective plurality of local nodes to the further switch or switches;
 - (c) providing a network routing algorithm to control the routing in the network;and
 - (d) dividing the connections from the at least one mesh node to the switches of the other mesh nodes between the switch or switches and the further switch of the at least one mesh node.
6. A method of upgrading a telecommunications network as claimed in Claim 5, further including the step of making a connection between the switches of the at least one mesh node.

7. A method of upgrading a telecommunications network as claimed in Claim 4 and substantially as hereinbefore described and as illustrated in Figures 3, 4, 5 and 6 of the accompanying drawings.

ABSTRACT

A telecommunications network having a plurality of mesh nodes, where each mesh node includes one or more switches and at least one of the mesh nodes includes a plurality of switches, each mesh node having a connection to each other mesh node and each mesh node having associated with it a respective plurality of local nodes, each switch of each mesh node being connected to all of the respective associated plurality of local nodes. The network may be upgraded by adding a further switch to a mesh node and connecting all the respective local nodes to that switch and sharing the connections between the switches of the mesh node. A suitable network routing algorithm controls the routing in the network.




Fig.1.






Fig.2.








Fig.5.




Fig.6.